



10K TYPE 11 ROOM SENSOR

SRT3-10KT2

The SRT3-10KT2 is intended for use as a room mounted temperature sensor designed in a modern neutral unobtrusive housing. The sensor is suitable for temperature controllers or BMS systems compatible with 10K type11 resistance sensors .



Made in Australia
100% Australian Owned Company

Thermistor Resistance Characteristics

TEMP	OHMS	TEMP	OHMS	TEMP	OHMS	TEMP	OHMS
5.0	25339	14.0	16465	23.0	10923	32.0	7402
6.0	24172	15.0	15698	24.0	10450	33.0	7097
7.0	23016	16.0	15001	25.0	10000	34.0	6807
8.0	21921	17.0	14324	26.0	9572	35.0	6530
9.0	20885	18.0	13683	27.0	9165	36.0	6266
10.0	19872	19.0	13073	28.0	8777	37.0	6014
11.0	18973	20.0	12488	29.0	8408	38.0	5774
12.0	18092	21.0	11943	30.0	8056	39.0	5544
13.0	17257	22.0	11420	31.0	7721	40.0	5325

Removing lid : once sensor installed , it is possible to remove lid without a tool simply by gently tugging on lid to pull out from base, otherwise gently apply slight pressure to right hand side with a pen or screwdriver on locking pin located in central grill on right hand side of base, note excessive pressure will break this locking pin.

Environmental Conditions

Operation

Ambient Temperature	0...45oC
Humidity	< 95 % RH (Non Condensing)

Storage and Transport

Ambient Temperature	-5...65oC
Humidity	< 90 % RH (Non Condensing)

Weight

Including Packaging	150 grams
---------------------	-----------

Housing

Colour	WHITE
Material	POLYCARBONATE
UV Stabilised	YES
Fire Retardant	YES
Size	L81mm x W81mm x D28mm
Mounting Method	Wall mount 4 screw locations